



New Data Confirms Gold Potential

Vancouver, BC June 21, 2010 Lovitt Resources Inc. (“the Company”) is pleased to announce that it is planning a diamond drilling program on the patented claims of its wholly owned Lovitt Gold Mine in Wenatchee, WA. The purpose of the program will be to develop a commercial NR43-101 ore reserve by targeting areas rich in historic data. The company recently discovered a set of Krig diagrams generated by Asamera Minerals Inc. with data developed from hundreds of diamond drill cores drilled from underground in the Lovitt Mine. in the 1980’s. Asamera had optioned part of the Lovitt Mine with the objective to develop ore to extend the life of its directly adjoining Cannon Mine. The “Krigs” are 20 ft x 20 ft x 50 ft blocks of 1554 short tons each and each block was assigned a gold grade based on at least five samples per block. This process defined several hundred thousand tons of open pit material in the first two thirds of the patented claims, over a vertical distance of 500 feet and a width of 600 feet. The company plans to drill the higher grade blocks to define commercial grades to an average of at least 0.20 oz/ton or 6.86 gm/t. There is further potential for ore to depth, and to the northeast within the patented claims. Analysis to date shows the concentration of gold in two distinct blocks, Block 1 in the first 700 feet from the 1250 portal, and Block 2 between 1,400 feet and 1,800 feet. Initial calculations show the possibility of 257,180 tons of .205 oz Au/ton (7.02 gm/t) in Block 1, and 131,761 tons of .208 oz Au/ton (7.12 gm/t) for 52,773 ounces in Block 1 and 27,420 ounces in Block 2, or total potential gold of 80,193 ounces. Block 3 in the back third of the mine was not explored by Asamera, but the company sampled this area extensively over the past two years, as recently reported in a news release dated March 15, 2010.

These resources are historic in nature and pre-date NI 43-101 requirements, so cannot be relied upon, but introduce new data which is consistent with geologic estimates by consultants in every report tendered between 1982 and 2009. This news release was reviewed and approved by our Director James Proudfoot, P Eng., a qualified person under NI 43-101.

The Lovitt Gold Mine was the 6th largest gold mine in the USA when it suspended operations in 1967 after producing 420,000 oz of gold and 620,000 oz of silver over a seventeen year period with an average grade of 0.40 oz of gold per ton (or 13.7 gm Au/t). The directly adjoining Cannon Mine produced 1,200,000 oz of gold and over 1,900,000 oz of silver at an average grade of 0.30 oz Au/ton (or 10.3 gm Au/t) between 1984 and 1995.

For more detailed information, please refer to the website of the Company at: <http://www.lovittresources.com> eMail: info@lovittresources.com or call Lorne Brown the President of the Company at (509)668-8170.

The TSX Venture Exchange has not reviewed, nor has it accepted responsibility for the adequacy or accuracy of the contents of this news release, which was prepared by management of the Company.